



BOOSTER MODEL 1214

The most powerful single stage booster in our fleet and the world. With exceptional air cooling features this booster is capable pressures up to 1400 psi with 1200 cfm flow volume with low exit temp. Whether for testing pipelines in Russia or the Middle East, or for reaching crazy RC drilling depths the ARC 1214 will not disappoint.

For the past three decades, Air Research Compressors have been building and supplying booster compressors to both the mining and drilling industries to increase depth capacity with faster penetration rates, longer bit life and greater efficiency.

Applications for our Boosters include mineral exploration and blast hole drilling, water well and geothermal drilling, oil and gas air/foam drilling, and pipeline services.

BOOSTER MODEL 1214

Standard Features

- On board fuel tank
- Booster bypass manifold (single stage)
- Two-way concentric valves
- Automatic scrubber tank drain valve
- Over speed shutdown valve
- Inlet particle filter
- Water cooled booster block
- Pre-cooler bypass system
- Inlet suction manifold
- Discharge temperature sensor
- Pre-cooler (30°C) & suction scrubber tank
- Aftercooler (60°C) max operating temperature
- Low pressure switch at booster inlet
- Open skid with fork lift slots
- 24 volt DC starting and operating system
- Suction and discharge safety relief valves
- Full function digital instrument panel monitoring all pressures, temperatures and controls with full protection shutdown and fault indicators
- Reduced air exit temperatures

Specifications

Booster type	4 cylinders, reciprocating
Configuration	INTEGRAL
Model	ARC 1214 8V92T
Drive engine	Detroit Diesel - 8V92T
Power	210bhp@1800 rpm
Booster stages	1
Max suction pressure (psi / bar)	450 / 31
Max discharge pressure (psi / bar)	1400 / 96.5
Capacity at maximum suction pressure (cfm / m3/min / l/sec)	1200 / 34 / 566
Booster oil capacity (gal / l)	See Engine
Engine oil capacity (gal / l)	6.6 / 25
Fuel tank capacity (gal / l)	105.7 / 400
Max operating ambient temp. (°F / °C)	125 / 52
Wet weight (lb / kg) - (approximate)	6614 / 3000
Overall dimensions, L x W x H (in / mm)	6'3" x 4'11" x 6'9" / 1900 x 1500 x 2050
Suction connection	50mm (2") BSP
Discharge connection	40mm (1 1/2") BSP

Options

- Fully clad with roof
 - Top lift feature
 - Engine speed adjustment
 - Trailer mounted unit
 - Lights for night operation
 - Extreme cold weather start kit
 - Spark arrestor
 - Insulation package to canopy
 - Service packs 250/500/1000/2000 hours
 - Valve and piston kits
- Other options, pressures, capacities:
available on request



Air Research Australia Pty Ltd
PO Box 23, Coleambally NSW 2707 Australia
Email: admin@ARCbooster.com
Phone: 1300 165 535 - International: +61 414 355 406
Web: ARCbooster.com